



Ag.: Asrep International

Tel: +39 333 6137934

Website: www.asrepi.com

Fax:

E-Mail: sales@asrepi.com

Contact: Beniamino Bendinelli

MP: 0039 333 6137934

MSN:

Skype: mirkoz75

Split solar flat plate water heater(water tank with two copper coils)

Model	SS-F2 150(with one collector)	SS-F2 200(with one collector)	SS-F2 250(with two collectors)	SS-F2 300(with two collectors)	SS-F2-400(with three collectors)	SS-F2 500(with three collectors)
-------	-------------------------------	-------------------------------	--------------------------------	--------------------------------	----------------------------------	----------------------------------

Solar collector	Core material	copper					
	Coating	Cooper cover coating of blue titanium which made in Germany Absorption rate: $\alpha=0.95$ Reflection rate $\epsilon=0.04$.					
	Base plate of panel	Marine-grade H3004 Aluminum toughnessH32 Thickness 0.7mm					
	Glass of panel	Special glass for panel With ANS1297-1-1975, BS6206A and JIS R3206 standards; toughness with AS2208-1978 and federal standards of United States.					
	Panel Insulation	Bottom with fiberglass insulation ,Thickness 60mm,Density 20kg/m ³ Side-thickness insulation:13mm Density 23kg/m ³ Thermal properties: R1.0 Thermal conductivity : 0.059W/m					
tank	Volume	150L	200L	250L	300L	400L	500L
	Insulating Layer	Polyurethane Foaming ,Thickness 45mm-50mm					
	Outer Tank	Color Steel Plate(enamel white) Thickness 0.53mm					
	Inner tank	tank: stainless steel 304; Thickness 1.2-1.5mm; Normal working pressure: 6 bar; Test pressure: 12 bar;					
workstation	Circulation Pump	RS-15/6 WILO					
	Controller	SR868C8					
	Expansion tank	5L	8L	8L	12L	12L	18L

