

Non-Pressure system



Ag.: Asrep International

Tel: + 39 333 6137934

Website: www.asrepi.com

Fax:

E-Mail: sales@asrep.com

Conatct: Mr Beniamino Bendinelli

MP: 0039 333 6137934

MSN:

Skype:

Non-Pressure system

Model	Evacuated tube		Collecting area(m2)	Tank		Material of Bracket	Material of inner and outer tank	Heat insulating layer	Application people Qty	Loading Qty (set)			Price (€)
	Dia(mm)	Len(m)		Dia outer/inner (mm)	Volume (L)					20'	40'	40'HQ	
SD-A1-16	47	1,5	1,42	420/310	104	Aluminium alloy, 1.4mm thickness	Inner tank: stainless steel 304-2B, 0.43mm thickness Outer tank: color steel plate, 0.43mm thickness	55mm thickness polyurethane foame	1,2	64	125	161	384
SD-A1-18	47	1,5	1,6	420/310	117				2	60	116	144	417
SD-A1-20	47	1,5	1,78	420/310	130				2,3	56	105	136	447
SD-A1-24	47	1,5	2,15	420/310	156				2,3	47	91	115	487
SD-A1-28	47	1,5	2,5	420/310	182				3	42	84	101	520
SD-A1-30	47	1,5	2,69	420/310	195				3	37	76	89	547
SD-A1-36	47	1,5	3,23	420/310	234				3,4	26	55	78	572
SD-A2-16	58	1,8	2	470/360	160				3	40	80	95	480
SD-A2-18	58	1,8	2,25	470/360	180				3	37	74	90	528
SD-A2-20	58	1,8	2,5	470/360	200				3,4	35	70	85	570
SD-A2-24	58	1,8	3,01	470/360	240				4	29	58	70	678
SD-A2-28	58	1,8	3,52	470/360	280				4,5	26	52	62	765
SD-A2-30	58	1,8	3,75	470/360	300				5	25	50	60	810
SD-A2-32	58	1,8	4	470/360	320				6	24	48	58	852
SD-A2-36	58	1,8	4,5	470/360	360				7	20	40	48	945



Model:SD-A



Non-Pressure system

Model	Evacuated tube		Collecting area(m2)	Tank		Material of Bracket	Material of inner and outer tank	Heat insulating layer	Application People Qty	Loading Qty (set)			Price(US\$)
	Dia(mm)	Len(m)		Dia outer/inner (mm)	Volume (L)					20'	40'	40'HQ	
SD-G1-16	47	1,5	1,42	420/310	104	Galvanized steel plate with plastic spraying, 1.4mm thickness	Inner tank: stainless steel 304-2B, 0.43mm thickness Outer tank: color steel plate, 0.43mm thickness	55mm thickness polyurethane foam	1,2	64	125	161	357
SD-G1-18	47	1,5	1,6	420/310	117				2	60	116	144	390
SD-G1-20	47	1,5	1,78	420/310	130				2,3	56	105	136	417
SD-G1-24	47	1,5	2,15	420/310	156				2,3	47	91	115	480
SD-G1-28	47	1,5	2,5	420/310	182				3	42	84	101	555
SD-G1-30	47	1,5	2,69	420/310	195				3	37	76	89	585
SD-G1-36	47	1,5	3,23	420/310	234				3,4	26	55	78	687
SD-G2-16	58	1,8	2	470/360	160				3	40	80	95	453
SD-G2-18	58	1,8	2,25	470/360	180				3	37	74	90	492
SD-G2-20	58	1,8	2,5	470/360	200				3,4	35	70	85	534
SD-G2-24	58	1,8	3,01	470/360	240				4	29	58	70	636
SD-G2-28	58	1,8	3,52	470/360	280				4,5	26	52	62	711
SD-G2-30	58	1,8	3,75	470/360	300				5	25	50	60	756
SD-G2-32	58	1,8	4	470/360	320				6	24	48	58	798
SD-G2-36	58	1,8	4,5	470/360	360				7	20	40	48	882



Non-Pressure system

Model	Evacuated tube		Collecting area(m2)	Tank		Material of Bracket	Material of inner and outer tank	Heat insulating layer	Application People Qty	Loading Qty (set)			Price(US\$)
	Dia(mm)	Len(m)		Dia outer/inner (mm)	Volume (L)					20'	40'	40'HQ	
SD-S1-16	47	1,5	1,42	420/310	104	stainless steel 304, 1.2mm thickness	Inner tank: stainless steel 304-2B, 0.43mm thickness Outer tank: stainless steel 304-2B, 0.43mm thickness	55mm thickness polyurethane foam	1,2	64	125	161	507
SD-S1-18	47	1,5	1,6	420/310	117				2	60	116	144	537
SD-S1-20	47	1,5	1,78	420/310	130				2,3	56	105	136	585
SD-S1-24	47	1,5	2,15	420/310	156				2,3	47	91	115	687
SD-S1-28	47	1,5	2,5	420/310	182				3	42	84	101	786
SD-S1-30	47	1,5	2,69	420/310	195				3	37	76	89	840
SD-S1-36	47	1,5	3,23	420/310	234				3,4	26	55	78	987
SD-S2-16	58	1,8	2	470/360	160				3	40	80	95	582
SD-S2-18	58	1,8	2,25	470/360	180				3	37	74	90	639
SD-S2-20	58	1,8	2,5	470/360	200				3,4	35	70	85	702
SD-S2-24	58	1,8	3,01	470/360	240				4	29	58	70	822
SD-S2-28	58	1,8	3,52	470/360	280				4,5	26	52	62	945
SD-S2-30	58	1,8	3,75	470/360	300				5	25	50	60	1008
SD-S2-32	58	1,8	4	470/360	320				6	24	48	58	1071
SD-S2-36	58	1,8	4,5	470/360	360				7	20	40	48	1185



Model:SD-S

