

ASREP TIONAL
INTERNA S.R.L.

ELECTRIC BIKES

Electric bikes (20inch/ruote piccole 510 mm diam. Folding/ pieghevoli) UNISEX

HED 7501 F



Motor:	250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	20"×1.95", puncture resistant K-shield(kenda)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	disc brakes
	Option: 24V 9ah /36v,9ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 30-35km,(9ah)	Chainguard:	Transparent ABS
	Pedaling-Electric mode 50-55km	Mudguard:	ABS
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3 kgs	Chain:	Rust resistant chain
N.W./G.W. :	21kgs/26kgs	Stander:	Al alloy central stander
Product Size:	1500X590X870 mm	Rear carrier:	Al alloy
Carton Size :	1390X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	114pcs/20' , 220pcs/40' , 250pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED 7501 J



Motor:	250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	20"×1.95", puncture resistant K-shield(kenda)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	V brakes
	Option: 24V 9Ah or 36V 9Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Al alloy
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 30-35km,(9ah)	Chainguard:	Transparent ABS
	Pedaling-Electric mode 50-55km	Mudguard:	ABS
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 2.5 kgs	Chain:	Rust resistant chain
N.W./G.W. :	20kgs/25kgs	Stander:	Al alloy central stander
Product Size:	1500X590X870 mm	Rear carrier:	Al alloy
Carton Size :	1390X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	114pcs/20' , 225pcs/40' , 250pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

Electric bikes (20inch/ruote GRANDI 660 mm diam.)(NOT Folding/NON pieghevoli) UNISEX

HED-7503 D



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	—	Tyres:	26"×2.125", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 9Ah, 36V 9Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 35-38km,	Chainguard:	
	Pedaling-Electric mode 50-55km	Mudguard:	NONE
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.3 kgs(24v8ah)	Chain:	Rust resistant chain
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1885*650*1110 mm	Rear carrier:	Al alloy
Carton Size :	1600X275X740 mm	Saddle :	GEL Cruiser saddle
Capability :	99pcs/20', 201pcs/40', 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED -7503 E



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 10Ah,36v10ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 45-50km,	Chainguard:	
	Pedaling-Electric mode 50-55km	Mudguard:	NONE
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 2.6 kgs(36v9ah)	Chain:	Rust resistant chain
N.W./G.W. :	20kgs/25kgs	Stander:	Al alloy central stander
Product Size:	1720*650*1070 mm	Rear carrier:	Al alloy
Carton Size :	1400X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	99pcs/20', 201pcs/40', 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7503 F



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
Battery :	Option: 24V 10Ah,36v10Ah,36V,16Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	pedaling-electric mode 50-60km,	Chainguard:	
		Mudguard:	ABS
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.8 kgs(36v9ah)	Chain:	Rust resistant chain(PYC)
N.W./G.W. :	23kgs/28kgs	Stander:	Al alloy central stander(GS)
Product Size:	1720*650*1070 mm	Rear carrier:	Al alloy
Carton Size :	1400X270X740 mm	Saddle :	GEL Cruiser saddle
Capabillity :	88pcs/20' , 148pcs/40' , 190pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7504 A



Motor:	250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061
PAS Controller:	Inner Intelligent Torque Sensor PAS	Tyres:	26"×1.75", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26"×1.5" Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
Battery :	Option: 24V 10Ah or 36V 10Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 35-40km,	Chainguard:	Transparent ABS
	PAS/Pedaling-Electric mode55- 65km	Mudguard:	plastic-aluminum
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.3 kgs (24V 10Ah)	Chain:	Rust resistant chain
N.W./G.W. :	22kgs/27kgs	Stander:	Al alloy central stander
Product Size:	1870X570X900 mm	Rear carrier:	Al alloy
Carton Size :	1600X275X740 mm	Saddle :	GEL Cruiser saddle
Capabillity :	96pcs/20' , 190pcs/40' , 220pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7504 F



Motor:	250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	-	Tyres:	24"×1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	disc brakes
Battery :	Option: 24V 10Ah or 36V 10Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 0.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 25-35km,	Chainguard:	-
	Pedaling-Electric mode 45-55km	Mudguard:	plastic-aluminum
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.3 kgs(24V 10Ah)	Chain:	Rust resistant chain
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1870X570X900 mm	Rear carrier:	Al alloy
Carton Size :	1600X275X740 mm	Saddle :	GEL Cruiser saddle
Capability :	81pcs/20' , 171pcs/40' , 192pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7504 H



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	-	Tyres:	26"×1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	V brakes
Battery :	Option: 24V 10Ah, 36V 10Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	3-class Shimano(inside)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 45-48km,	Chainguard:	Transparent ABS
	Pedaling-Electric mode 50-55km	Mudguard:	ABS
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.5 kgs(24v10ah)	Chain:	Rust resistant chain
N.W./G.W. :	25kgs/31kgs	Stander:	Al alloy central stander
Product Size:	1750*650*1030 mm	Rear carrier:	Al alloy
Carton Size :	1600X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	82pcs/20' , 194pcs/40' , 210pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7504 I



Motor:	250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061,
Controller:	—	Tyres:	26"×2.125", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
Battery :	Option: 24V 9Ah, 36V 9Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 35-38km,	Chainguard:	
	Pedaling-Electric mode 50-55km	Mudguard:	NONE
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3.3 kgs(24v8ah)	Chain:	Rust resistant chain
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1885*650*1110 mm	Rear carrier:	Al alloy
Carton Size :	1600X275X740 mm	Saddle :	GEL Cruiser saddle
Capability :	99pcs/20' , 201pcs/40' , 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED-7505 NEW



Motor:	250w High Speed Brushless Gear motor	Frame:	Al Alloy 6061
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26"×1.5" Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
Battery :	Option: 24V 10-15Ah or 36V 10-15Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 25-35km,(10ah)	Chainguard:	—
	Pedaling-Electric mode 45-55km (10ah)	Mudguard:	
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 2.5 kgs(24V 10A)	Chain:	Rust resistant chain
N.W./G.W. :	22kgs/27kgs	Stander:	Al alloy central stander
Product Size:	1870X570X900 mm	Rear carrier:	
Carton Size :	1600X275X740 mm	Saddle :	velo
Capability :	96pcs/20' , 191pcs/40' , 210pcs/40' HQ	Seat Post :	foldable

Electric bikes (26 inch/ruote GRANDI 660 mm diam.)(Folding/ pieghevoli)



HED 7502



HED 7502 A



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	-	Tyres:	26"x1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5", Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 9Ah, 36v 9Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension, Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 35-38km,	Chainguard:	NONE
	Pedaling-Electric mode 50-60km	Mudguard:	NONE
Load capacity:	120kg	Chainwheel :	Steel 44 T, Al alloy crank
Weight::	Li-ion battery 3.3 kgs(24v9ah)	Chain:	Rust resistant chain
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1750*650*1030 mm	Rear carrier:	Al alloy
Carton Size :	1390X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	99pcs/20' , 201pcs/40' , 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	-	Tyres:	26"x1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5", Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 9Ah, 36v 9Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	7-class Shimano(TX-55)
	Charge time 4-6 hours	Front fork:	Suspension, Al alloy double crown(ZOOM)
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 35-38km,	Chainguard:	NONE
	Pedaling-Electric mode 50-60km	Mudguard:	NONE
Load capacity:	120kg	Chainwheel :	Steel 44 T, Al alloy crank
Weight::	Li-ion battery 3.3 kgs(24v9ah)	Chain:	Rust resistant chain
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1750*650*1030 mm	Rear carrier:	Al alloy
Carton Size :	1390X270X720 mm	Saddle :	GEL Cruiser saddle
Capability :	99pcs/20' , 201pcs/40' , 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

HED 7502 A new



Motor:	180-250W High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield(CST)
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Option: 24V 9Ah, 36v 9Ah Li-ion battery	Brakes(front):	Disc brakes
	Overload protection ,Low voltage protection	Brakes(Rear):	Disc brakes
Charger :	Option: 24V 9Ah, 36v 9Ah Li-ion battery	Gears:	7-class Shimano(TX-55)
	100-240VAC50-60HZ, 1.8A amps smart charger	Front fork:	Suspension,Al alloy double crown(ZOOM)
Max Speed :	Charge time 4-6 hours	Handle bars:	Al Alloy (ZOOM)
Range:	≤25Km/h	Chainguard:	NONE
	e-bike mode 35-38km,	Mudguard:	NONE
Load capacity:	Pedaling-Electric mode 50-60km	Chainwheel :	Steel 44 T,Al alloy crank
	120kg	Chain:	Rust resistant chain
Weight::	Li-ion battery 3.3 kgs(24v9ah)	Stander:	Al alloy central stander
N.W./G.W. :	24kgs/29kgs	Rear carrier:	Al alloy
Product Size:	1750*650*1030 mm	Saddle :	GEL Cruiser saddle
Carton Size :	1390X270X720 mm	Seat Post :	Al alloy with suspension(ZOOM)
Capability :	99pcs/20' , 201pcs/40' , 225pcs/40' HQ		

HED 7502 B



Motor:	180-250w High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 9Ah, 36V 9Ah Li-ion battery	Brakes(Rear):	V brakes
Charger :	Option: 24V 9Ah, 36V 9Ah Li-ion battery	Gears:	7-class Shimano
	100-240VAC50-60HZ, 1.8A amps smart charger	Front fork:	Suspension,Al alloy double crown
Max Speed :	Charge time 4-6 hours	Handle bars:	Al Alloy (ZOOM)
Range:	≤25Km/h	Chainguard:	NONE
	e-bike mode 35-38km,	Mudguard:	NONE
Load capacity:	Pedaling-Electric mode 50-55km	Chainwheel :	Steel 44 T,Al alloy crank
	100kg	Chain:	CMK
Weight::	Li-ion battery 3.3 kgs(24v9ah)	Stander:	Al alloy central stander
N.W./G.W. :	24kgs/29kgs	Rear carrier:	NONE
Product Size:	1750*650*1030 mm	Saddle :	GS
Carton Size :	1390X270X720 mm	Seat Post :	Al alloy with suspension(ZOOM)
Capability :	99pcs/20' , 201pcs/40' , 225pcs/40' HQ		

HED 7502 B new



Motor:	180-250w High Speed Brushless Gear motor	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 10Ah, 36V 10Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	Shimano 21speed,rear:7s,front :3s
	Charge time 4-6 hours	Front fork:	Suspension,Al alloy double crown
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 38-40km,	Chainguard:	NONE
	Pedaling-Electric mode 55-60km	Mudguard:	NONE
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3 kgs(36v9ah)	Chain:	CMK
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1750*650*1030 mm	Rear carrier:	NONE
Carton Size :	1390X270X720 mm	Saddle :	GS
Capability :	99pcs/20', 201pcs/40', 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)

Electric TRICICLE (20inch/ruote piccole 510 mm diam.) (NOT Folding/ NON pieghevoli)

HED 7507 B



Motor:	DC brushless	Frame:	Al Alloy 6061, foldable
Controller:	—	Tyres:	26"×1.95", puncture resistant K-shield
	Pedaling Run/Pedaling-Electric Assist Run	Rim:	26*1.5",Al Alloy twin wall and CNC side wal
	Option: Pure Electric Run Model	Spokes:	13g steel
Battery :	Overload protection ,Low voltage protection	Brakes(front):	Disc brakes
	Option: 24V 10Ah, 36V 10Ah Li-ion battery	Brakes(Rear):	Disc brakes
Charger :	100-240VAC50-60HZ, 1.8A amps smart charger	Gears:	Shimano 21speed,rear:7s,front :3s
	Charge time3-4 hours	Front fork:	Suspension,Al alloy double crown
Max Speed :	≤25Km/h	Handle bars:	Al Alloy (ZOOM)
Range:	e-bike mode 38-40km,	Chainguard:	NONE
	Pedaling-Electric mode 55-60km	Mudguard:	NONE
Load capacity:	100kg	Chainwheel :	Steel 44 T,Al alloy crank
Weight::	Li-ion battery 3 kgs(36v9ah)	Chain:	CMK
N.W./G.W. :	24kgs/29kgs	Stander:	Al alloy central stander
Product Size:	1750*650*1030 mm	Rear carrier:	NONE
Carton Size :	1390X270X720 mm	Saddle :	GS
Capability :	99pcs/20', 201pcs/40', 225pcs/40' HQ	Seat Post :	Al alloy with suspension(ZOOM)